

ROPELIFE SERIES

Description:	Wire ropes require an effective boundary lubricant which will provide a combination of corrosion protection and extreme pressure lubrication. Ropelife wire rope dressing possesses all these necessary features and in addition will not clog the rope with congealed thickening agents or residues. Ropelife is a semi-fluid grease containing a blend of Molybdenum Disulphide and Graphite is formulated to protect and lubricate wire ropes by penetration of solid lubricants to the core of the rope, leaving a clean, non-drip, corrosion resistant coating. Ropelife Aerosol provides corrosion protection, penetrates and gives interstrand lubrication and greatly extends rope life.
Applications:	Heavily loaded rope of all kinds, e.g. dock side cranes, ships' cranes and derricks, haulage ropes and loading bay cranes etc.
Method of Application:	Brush, mop, spatula or specially designed spray system. Does not require heating prior to application in cold weather. If applied with an automatic wire rope lubrication system, select Ropelife AA.
Shelf Life:	Indefinite if unopened.
Approvals:	Naval Rate Book Number CED/SPT/211/24/49/11 NATO Stock Number 8030-99-594-0384 Class Group 0474 British Ropes (limited approval)

	ROPELIFE AEROSOL	ROPELIFE	ROPELIFE AA
General Description	Soft black grease	Soft black grease	Black fluid
Thickener	Organophilic clay	Organophilic clay	Calcium soap
Base Oil	Mineral oil	Mineral oil	Mineral oil
Dispersed Phase	A blend of high purity Graphite and Molybdenum Disulphide		
Solids Content	8.5%	8.5%	7%
Diluent	Methylene Chloride	-	-
TLV	250 ppm.	-	-
Flash Point (IP.35)	-	191°C	215°C
Penetration (IP50 ASTM 217-68)	-	300 - 350	-
Operating Temperature Range		- 30 to + 125 °C	

The above information reflects the current state of knowledge of our research. It cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for individual applications. Before using our products, therefore, check their suitability and be satisfied that the results will be satisfactory. Our products are continually being updated. We reserve the right, therefore, to alter the information on this product at any time and without prior announcement.



R J Mellor & Co Ltd

1 Devonshire Grove, Sheffield, South Yorkshire, England, S17 3PG
 Tele: +44 (0) 114 236 8666 Fax: +44(0) 114 236 3020
 E-mail: sales@rjmellor.co.uk Web: www.rjmellor.co.uk

